

LISTING OF AND AMENDMENTS TO CLAIMS:

1. (currently amended) Apparatus ~~{101}~~ for determining a pulse position for a signal encoded by pulse modulation, the signal comprising a first component ~~{PCS}~~ and a second component ~~{DCS}~~, the apparatus comprising:

a determination unit ~~{110}~~ comprising a probability table ~~{110}~~ for providing a value ~~{DDS}~~ representative of the pulse position in response to receipt of at least one symbol of the first component ~~{PCS}~~ and at least one symbol of the second component ~~{DCS}~~, wherein the first component is a first received signal having a first signal quality measure and the second component is a second received signal having a second signal quality measure, said probability table being an asymmetric probability table when said first signal component has a better quality measure than said second signal component, and said probability table being a symmetric probability table when said first signal component has an equal quality measure to said second signal component.

2. (currently amended) Apparatus according to claim 1 further comprising a first storage unit ~~{102}~~ for storing at least one symbol of the first component ~~{PCS}~~ and a second storage unit ~~{104}~~ for storing at least one symbol of the second component ~~{DCS}~~.

3. (currently amended) Apparatus according to claim 1, wherein the pulse position ~~{DDS}~~ is the most-likely pulse position.

4. (canceled)
5. (previously presented) Apparatus according to claim 1, wherein the probability table comprises a diagonally asymmetric table.
6. (currently amended) Apparatus according to claim 5, wherein in the case that the first component ~~{PGS}~~ shows a legal symbol then the second component ~~{DGS}~~ has no influence on the value.
7. (currently amended) Apparatus according to claim 1, wherein the quality of the first component ~~{PGS}~~ is better than that of the second component ~~{DGS}~~.
8. (previously presented) Apparatus according to claim 1, wherein the probability table comprises a diagonally symmetric table.
9. (currently amended) Apparatus according to claim 1, wherein the probability table ~~[[{(110)}]]~~ comprises more than two dimensions.
10. (currently amended) Apparatus according to claim 1, wherein the probability table ~~{110}~~ is storable in a memory ~~{118}~~, such as a read only memory ~~{ROM}~~ and/or a random access memory ~~{RAM}~~, and wherein two or more probability tables ~~{110}~~ are usable.
11. (currently amended) Apparatus according to claim 1, wherein the determination unit ~~{118}~~ derives the pulse

position {DDS} by a prestored formula, preferably a probability based formula, whereby the at least one symbol of the first component {PCS} and the at least one symbol of the second component {DCS} represent signal values for input to the formula.

12. (canceled)

13. (currently amended) Apparatus according to claim 25, wherein the means {122} for detecting an illegal symbol are logic circuits {122} or an extension of the probability table {110}.

14. (original) Apparatus according to claim 1, wherein the signal comprises an infrared signal.

15. (canceled)

16. (currently amended) A method for determining a pulse position for a signal encoded by a pulse modulation, the signal comprising a first component {PCS} and a second component {DCS}, the method comprising ~~the step of:~~

providing, via a probability table {110}, a value {DDS} representative of the pulse position in response to receipt of at least one symbol of the first component {PCS} and at least one symbol of the second component {DCS}, wherein the first component is a first received signal having a first signal quality measure and the second component is a second received signal having a second signal quality measure, said probability table being an

asymmetric probability table when said first signal component has a better quality measure than said second signal component, and said probability table being a symmetric probability table when said first signal component has an equal quality measure to said second signal component.

17. (currently amended) A method according to claim 16, further comprising the steps of storing at least one symbol of the first component {PCS} and storing at least one symbol of the second component {DCS}.

Claims 18, 19, 20 and 21 (all canceled).

22. (currently amended) A computer program comprising program code means for performing, when said program is run on a computer, a method for determining a pulse position for a signal encoded by a pulse modulation, the signal comprising a first component {PCS} and a second component {DCS}, the method comprising:

providing, via a probability table {110}, a value {DDS} representative of the pulse position in response to receipt of at least one symbol of the first component {PCS} and at least one symbol of the second component {DCS}, wherein the first component is a first received signal having a first signal quality measure and the second component is a second received signal having a second signal quality measure, said probability table being an asymmetric probability table when said first signal component has a better quality measure than said second

signal component, and said probability table being a symmetric probability table when said first signal component has an equal quality measure to said second signal component.

23. (currently amended) A computer program product comprising program code means stored on a computer readable medium for performing, when said program is run on a computer, a method for determining a pulse position for a signal encoded by pulse modulation, the signal comprising a first component {PCS} and a second component {DCS}, the method comprising:

providing, via a probability table {110}, a value {998} representative of the pulse position in response to receipt of at least one symbol of the first component {PCS} and at least one symbol of the second component {DCS}, wherein the first component is a first received signal having a first signal quality measure and the second component is a second received signal having a second signal quality measure, said probability table being an asymmetric probability table when said first signal component has a better quality measure than said second signal component, and said probability table being a symmetric probability table when said first signal component has an equal quality measure to said second signal component.

24. (currently amended) Apparatus {101} for determining a pulse position for a signal encoded by pulse modulation,

the signal comprising a first component {PCS} and a second component {DCS}, the apparatus comprising:

a determination unit {118} comprising a probability table {110} for providing a value {DDS} representative of the pulse position in response to receipt of at least one symbol of the first component {PCS} and at least one symbol of the second component {DCS}, wherein the probability table {110} is based on Bayes' probability.

25. (new) Apparatus {101} for determining a pulse position for a signal encoded by pulse modulation, the signal comprising a first component {PCS} and a second component {DCS}, the apparatus comprising:

a determination unit {118} comprising a probability table {110} for providing a value {DDS} representative of the pulse position in response to receipt of at least one symbol of the first component {PCS} and at least one symbol of the second component {DCS}, and

means for detecting an illegal symbol.

26. (previously presented) Apparatus {101} for determining a pulse position for a signal encoded by pulse modulation, the signal comprising a first component {PCS} and a second component {DCS}, the apparatus comprising:

a determination unit {118} comprising a probability table {110} for providing a value {DDS} representative of the pulse position in response to receipt of at least one

symbol of the first component {PGS} and at least one symbol of the second component {DCS}, wherein the pulse modulation comprises a four position pulse position modulation.

27. (new) Apparatus according to claim 1, wherein said pulse position is pulse position as a function of time.

28. (new) A method according to claim 16, wherein said pulse position is pulse position as a function of time.

29. (new) The computer program according to claim 22, wherein said pulse position is pulse position as a function of time.

30. (new) The computer program product according to claim 23, wherein said pulse position is pulse position as a function of time.

31. (new) Apparatus according to claim 25, wherein said pulse position is pulse position as a function of time.

32. (new) Apparatus according to claim 26, wherein said pulse position is pulse position as a function of time.

33. (new) Apparatus according to claim 1, wherein, said probability table is a first probability table when said first signal component has a better quality measure than said second signal component, and said probability table is a second probability table when said first signal component has an equal quality measure to said second signal component.